"Therec Corporation Ltd."

High Pressure Blower Capability









Our Fabricating Work Shop Facility

Roots (Positive Displacement) Blower Package








Pneumatics Conveying System

Combustion Air Supply for Cement Kiln







Waste Water Treatment System







Back Wash Air Blower



Aeration for Tiger Prawn Hatchery



Soybean Sauce Mixings Tank

















Acoustic Enclosure

Ring (Side Chanel) Blower Package







Printing Process

Bio-gas Boosting

Waste water Treatment









Central Vacuum Dust Collecting

High Pressure Centrifugal Blower Package











Multi-stage Centrifugal Blower









Fine Bubble Air Diffuser

Other Accessories












In-line filter

Air Cooling unit with out-let filter












Air converting device Pressure & Vacuum relief valve Swing Check valve

Air & Gas Handling System

Landfill gas boosting system, supply for power generator fully automatic operation with pressure, vaccum, temperature & gas sensor, control valve and PLC control panel with scada link to PC in control room







Process Diagram

Water trap tank

Flare



Installation on site



Roots gas blower



Gas cooler



Central air supply system for gas burner











Side channel gas blower with all accessories in ss 304 for bio-gas boosting system, from waste treatment plant to boilers gas burner

Oil Free Air Blower & Compre

DRESSER ROOTS



ROOTS










ดวามต้องการของถูกด้า

รทโบลว์เวอร์ (ROOTS BLOWER) Made in U.S.A

- แรงดันสูงสุด $= 20,000 \text{ mmH}_2\text{O}, 2.0 \text{ bar}$
- ปริมาณลมสูงสุด = 107,000 ลูกบาศ์กเมตร/ชม. (m³ / hr)
- สูญญูกาศต่ำสุด = -0.9 bar (สำหรับปั้มสูญญากาศ)

อุปกรณ์ประกอบและตู้เก็บ เสียงทำจากสแตนเลสใช้ ซานรับงานที่ต้ององใน บรรจากาศที่มีการกัดกร่อนสูง







ตู้เก็บเฉียงออกแบบพิเศษ ตามความตั้งงการของถูกค้า



🕜 ตู้เก็บเฉียงแบบประหยัดกับ Inline - Filter ขนาดใหญ่พิเศษ สำหรับระบบดูดผงสารเคมี

F.P.Z. effepizeta



รุ่นมาตรฐาน

รุ่นแรงดันสูงพิเศษ

รุ่นกันระเบิดสำหรับส่งแก๊สที่อันตราย (Standard High Pressure Type) (Super High Pressure) (Gas Tight Explosion Proof)



Pressure & Vacuum Relife Valve Size "2.0 - 4.0"

Pressure: 0.0 to 0.6 Bar (0-6,000 m Vacuum : 0.0 to -0.5 Bar

ริงโบลว์เวอร์ (RING BLOWER, SIDE CHANNEL BLOWER) Made in Italy

- ขนาด 0.5 ถึง 40 แรงม้า (HP)
- แรงดันสูงสุด = 7,250 mmH₂O, 0.725 bar
- ปริมาณลมสูงสุด = 1,800 ลูกบาศ์กเมตร/ชม. (m³ / hr)

BLOWER ग्रावीकी

บริษัท เทอร์เรค คอร์ปอเรชั่น จำกัด บริษัท เทอร์เรค คอร์ปอเรชั่น จำกัด THEREC CORPORATION LTD